

Kleenscreen Blackout

Solar Screen



TEXSTYLE



Kleenscreen Blackout

Kleenscreen Blackout combines the functionality and durability of a typical solar screen with the privacy of a 100% blackout fabric. Featuring Sanitized®, Kleenscreen Blackout inhibits the development of bacterial odors as well as the growth of mold and mildew on your fabric. Easy to weld and easy to clean, Kleenscreen Blackout provides a practical solution for any residential or commercial interior space.


Features

- 100% blackout solar screen
- Easy to clean
- Waterproof
- Flame Retardant to NFPA 701
- Easy to weld for internal hem bars, no tape required
- Color matched back makes it ideal for open roll systems
- GREENGUARD Gold Certified for low VOC emissions


Colors




ICE




BARLEY




PUMICE




ALLOY



SHALE



GRAPHITE



BLACK

Kleenscreen Blackout

Solar Screen



Specifications

	Blackout
Composition	25% Polyester, 75% PVC
Weight	16.96 oz/yd ² (575g/m ²)
Thickness	0.027in (.69mm)
Light fastness	Grade 4 (AATCC 16)
Average length	30 yd/roll (27.4m)
Width	118" (3m)
Cutting	Knife, Crush, Ultrasonic
Welding	No Tape. 248°F (120°C) to 284°F (140°C), Test First
Railroadable	Not Recommended
Cleaning	Wipe clean with warm soapy water and damp cloth
Fire Classifications	NFPA 701
Environmental Standards	GREENGUARD Gold, Environmental Product Declaration, Health Product Declaration, OEKO-TEX Standard 100, ISO 14001

Thermal and Optical Factors

	COLOR	THERMAL FACTORS			OPTICAL FACTORS		FABRIC & GLASS	
		Rs(%)	As(%)	Ts(%)	Rv(%)	Tv(%)	SHGC % Improvement	SHGC
Blackout	Ice	65	35	0	73	0	64	0.13
	Alloy	61	39	0	65	0	61	0.16
	Barley	58	42	0	61	0	60	0.17
	Pumice	50	50	0	54	0	57	0.20
	Shale	30	70	0	34	0	50	0.26
	Graphite	9	91	0	10	0	43	0.33
	Black	3	97	0	4	0	41	0.35



FR



LEAD FREE



FORMALDEHYDE FREE



WATERPROOF



EASY CLEAN



ANTI-BACTERIAL



ENERGY SAVING



PRINT ABLE