

X-Weave

Exterior Solar Screen



TEXSTYLE



X-Weave

Perfect for any application, X-Weave in both 5% and 10% openness offers privacy and sun protection while enhancing the look of your outdoor entertainment area.

Made with the outdoors in mind, X-Weave is a sturdy 2x2 weave that makes work-ability and versatility two of its strongest characteristics, allowing you to master outdoor living and comfort. This insect resistant exterior fabric collection pairs beautifully and durably with our Zipscreen Exterior system.


Features

- For Exterior and Interior use
- Insect Resistant
- Available in 5% and 10% Openness
- 126" Roll Width and Railroadable
- NFPA 701 Fire Classification
- Tear Strength: Warp 330N, Weft 210N
- 10 Year Warranty


Colors



WHITE




SUNRISE



SAND




FOSSIL




STONE GREY




GRAPHITE




SLATE



SUNSET



MAHOGANY



OBSIDIAN



ONYX

X-Weave

Exterior Solar Screen



Specifications

| | 5% | 10% |
|-----------------------------|--|----------------------|
| Composition | 30% Polyester, 70% PVC | |
| Openness Factor | Average 5% | Average 10% |
| Weight | 15.63 oz/yd ² (530g/m ²) | 13.86ozyd2 (470g/m2) |
| Thickness | 0.032in (.82mm) | 0.027in (.68mm) |
| Light Fastness | ≥ 5 (Blue wool scale) | |
| Average length | 22yd/roll (20m) | |
| Width | 126" (3.2m) | |
| Cutting | Crush, Cold, and Ultrasonic | |
| Welding | 248°F (120°C) to 284°F (140°C), test first | |
| Railroadable | Yes, but should be done for all shades in the room to avoid visual variation | |
| Cleaning | Wipe clean with warm soapy water and damp cloth | |
| Environmental Standards | GREENGUARD Gold, Environmental Product Declaration, Health Product Declaration, OEKO-TEX Standard 100, ISO 14001 | |
| Fungal/Bacterial Resistance | ASTM G21, ASTM E2149 | |
| Tensile Strength | Warp 2460N per 1.97" Weft 1690N per 1.97" | |
| Tearing Strength | Warp 330N Weft 210N | |
| Fire Classifications | NFPA 701 | |

X-Weave

Exterior Solar Screen



Thermal and Optical Factors

| COLOR | | THERMAL FACTORS | | | OPTICAL FACTORS | | FABRIC & GLASS | |
|-------|------------|-----------------|----|----|-----------------|----|--------------------|------|
| | | Rs | As | Ts | Rv | Tv | SHGC% Improvements | SHGC |
| 5% | White | 70 | 12 | 18 | 76 | 16 | 61 | 0.21 |
| | Sunrise | 49 | 40 | 11 | 51 | 10 | 51 | 0.25 |
| | Fossil | 23 | 68 | 9 | 24 | 9 | 40 | 0.33 |
| | Graphite | 14 | 72 | 14 | 14 | 14 | 20 | 0.36 |
| | Mahogany | 7 | 84 | 9 | 7 | 8 | 34 | 0.38 |
| | Obsidian | 6 | 86 | 8 | 5 | 9 | 30 | 0.38 |
| | Onyx | 3 | 90 | 7 | 4 | 7 | 26 | 0.38 |
| | Sand | 51 | 32 | 17 | 52 | 13 | 15 | 0.27 |
| | Slate | 8 | 83 | 9 | 8 | 8 | 20 | 0.37 |
| | Stone gray | 30 | 59 | 11 | 30 | 9 | 17 | 0.32 |
| | Sunset | 11 | 80 | 9 | 11 | 9 | 21 | 0.36 |
| 10% | White | 66 | 12 | 22 | 71 | 21 | 56 | 0.25 |
| | Sunrise | 48 | 36 | 16 | 49 | 16 | 48 | 0.28 |
| | Fossil | 21 | 59 | 20 | 22 | 20 | 35 | 0.38 |
| | Graphite | 15 | 65 | 20 | 15 | 19 | 20 | 0.39 |
| | Mahogany | 7 | 80 | 13 | 7 | 13 | 21 | 0.39 |
| | Obsidian | 7 | 80 | 13 | 7 | 12 | 20 | 0.39 |
| | Onyx | 3 | 84 | 13 | 4 | 13 | 20 | 0.39 |
| | Sand | 47 | 31 | 22 | 49 | 19 | 26 | 0.31 |
| | Slate | 8 | 78 | 14 | 8 | 14 | 20 | 0.39 |
| | Stone gray | 28 | 58 | 14 | 29 | 13 | 18 | 0.33 |
| | Sunset | 12 | 73 | 15 | 12 | 14 | 20 | 0.38 |



FR

LEAD FREE

FORMALDEHYDE
FREE

PHTHALATE
FREE

FRAGRANCE
FREE

ANTI-
BACTERIAL

ENERGY
SAVING

INSECT
RESISTANT