

### 4700 P

4700 P Solar Screen fabrics offer a fire retardant stylish and modern aesthetic for window treatments that minimize the negative effects of the sun, while preserving outward visibility


The 4700 P series is our heaviest screen and offers an openness factor of less than 1%, making it the perfect choice when maximum privacy is desired.

### **FEATURES**

- Thick yarns provide strong tensile and tear strength along with interesting texture
- Adds privacy to any space
- GREENGUARD Gold ceritifed for low VOC emissions
- OEKO-TEX Standard 100 Certified
- Limited Lifetime Warranty

## **COLORS**





WHITE/WHITE WHITE/BEIGE



# Solar Screen



## **SPECIFICATIONS**

	<1%
Composition	20 Polyester, 80% PVC
Weight	18.58oz/yd² (630 g/m²),+/- 5%
Thickness	0.035 in (.9mm)
Light Fastness	Grade 8
Average length	33 yd/roll (30m)
Width	98.4" (2.5m)
Cutting	Cold, Crush, and Ultrasonic
Welding	248°F (120°C) to 284°F (140°C)
Railroadable	No
Cleaning	Wipe clean with warm soapy water and damp cloth.
Environmental Standards	GREENGUARD Gold, CDPH Standard Method v1.1-2010, OEKO-TEX Certified 100, ISO 14001
Fungal/Bacterial Resistance	ASTM E2180, G21, G22
Fire Classifications	NFPA 701, CA Title 19

		OPTICAL FACTORS					
COLOR	Ts	Rs	As	Shading Coefficient			т.,
				1/8" CL	1/4" CL	1/4" HA	Tv
P001 White/White	13	74	13	0.27	0.27	0.29	7
P012 White/Beige/Beige	9	65	26	0.32	0.32	0.31	5

































ANTI-





**LEAD FREE** 

**FORMALDEHYDE FREE** 







